



TECHNICAL DATA SHEET

Order reference		ОР30-Р-Е				
Article number		8137	55			
Date	4-11-1	1	Replaces	03-31-08	No. Pages	1

Product Description:

I Touuci Description.		
Style	Blanket Roll; high strength perforation every 76 cm for single or	
	multiple/variable length pads	
Item Size (each)	76 cm wide by 46 m long (60 Pads)	
Color	White	
Composition	100% Polypropylene	
Structure	96% natural white meltblown nonwoven fibers(<10 microns)	
	4% white spunbond nonwoven coverstock(<15-30 microns)	
Technology	Meltblown + spunbond	
Absorbency	Hydrophobic + Oleophilic	
Bonding	Bonded (staggered pattern) + Mechanical entanglement	
Intended Application	Low -Lint Chemical Resistant Sorbent for Oil or Solvent Base Liquids	

Absorbency Capacity 187 1 per Roll (saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	1 Case	Pkg. Weight	14.6 kg (12.9 kg)
Items per Package	1 Roll / Case (60 Pads)	Pkg. Dimensions	45.5cm x 45.5cm
			x 79cm H
Container type	Carton		

Physical Properties;

Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	g/m2	365	36
Caliper	SPCTM-020	mm	5.4	0.5
Absorbency** (med.	SPCTM-004B	gL/gS	12.5	2
Oil)				
Tensile Strength	SPCTM-007	daN	13.8	1.3
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	
Brady Europe Industriepark C3 Lindestraat 20 B9240 Zele Belgium		

Tel: +32 52.45.7811 | Fax: +32 52.45.7812

www.bradyeurope.com